## **AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

## **LISTING OF CLAIMS:**

Claims 1-21 (Canceled)

22. (Currently Amended) The reactor according to Claim 40 39, wherein said second bundle is formed by at least two segments of tubes wound along helical generatrices, nested and extending in parallel between said distributor and said manifold.

23. (Previously Presented) The reactor according to Claim 39, wherein said bundle is formed by three segments of tube wound along helical generatrices and nested.

24. (Previously Presented) The reactor according to Claim 39, wherein said segments have substantially the same length and/or induce substantially the same pressure drop on the flow of said coolant fluid, between said distributor and said manifold.

25. (Canceled)

- 26. (Currently Amended) The reactor according to Claim 25 39, wherein said distributor and/or said manifold being in the form of a torus and centered on said axis.
  - 27. (Canceled)
  - 28. (Canceled)
  - 29. (Canceled)
- 30. (Previously Presented) A reactor according to Claim 39, further comprising an agitator arranged around or inside said coil.
- 31. (Previously Presented) A reactor according to Claim 30, wherein said agitator is suspended from a ceiling of said reactor and forms a cage surrounding said coil the supply and evacuation of the coolant fluid towards or from said coil being effected through the bottom of said reactor.
  - 32. (Canceled)
- 33. (Currently Amended) A reactor according to Claim 40 39, wherein the radius of said second bundle is less than that of said first bundle and being between 20 and 70% of the radius of said inner volume.

- 34. (Previously Presented) A reactor according to Claim 33, wherein the radius of said second bundle is between 20 and 40% of said radius of said inner volume.
- 35. (Previously Presented) A process for the treatment of a viscous medium comprising the step of treading said liquid in a reactor as defined in Claim 39 and of an inner volume greater than about 8m<sup>3</sup>.
- 36. (Previously Presented) The process according to Claim 35, wherein said treatment is a reaction of polymerization.
- 37. (Previously Presented) The process according to Claim 36, wherein the reaction is a discontinuous reaction of polymerization.
- 38. (Previously Presented) The process according to Claim 36 wherein the reaction is a continuous reaction of polymerization.
- 39. (Currently Amended) A reactor for treating a viscous medium or for carrying out chemical reactions in viscous medium, said reactor comprising:

a vessel defining an inner volume; and

a coil in said inner volume for circulation of a coolant fluid, said coil comprising a first segment of tube wound along a helical generatrix, and a second

Attorney's Docket No. 1022702-000256 Application No. 10/502,178

Page 5

segment of tube wound along a helical generatrix and extending in parallel to

the first segment between a distributor and a manifold, said first and second

segments being centered on the same geometrical axis with substantially the

same bending radius and nested so that they together form a substantially

cylindrical bundle; wherein the distributor is located within said inner volume

and is curved with a radius substantially equal to the bending radius; the

distributor arranged substantially coaxially with the bundle;

wherein the bundle constitutes a first bundle the coil further comprising

a second bundle of cylindrical shape centered on said axis and curved

with a radius different from said radius of said first bundle;

wherein the coil further comprises a tube extending in a direction

substantially parallel to said axis between said first and second

bundles, said tube being connected either to said distributor or to said

manifold.

40. (Canceled)

41. (Currently Amended) A reactor for treating a viscous medium or

for carrying out chemical reactions in viscous medium; said reactor comprising:

a vessel defining an inner volume; and

a coil in said inner volume for circulation of a coolant fluid, said coil comprising a first segment of tube wound along a helical generatrix, and a second segment of tube wound along a helical generatrix and extending in parallel to the first segment between a distributor and a manifold, said first and second segments being centered on the same geometrical axis with substantially the same bending radius and nested so that they together form a substantially cylindrical bundle; wherein the manifold is located within said inner volume and is curved with a radius substantially equal to the bending radius; the manifold arranged substantially coaxially with the bundle;

wherein the bundle constitutes a first bundle the coil further comprising a second bundle of cylindrical shape centered on said axis and curved with a radius different from said radius of said first bundle;

wherein the coil further comprises a tube extending in a direction substantially parallel to said axis between said first and second bundles, said tube being connected either to said distributor or to said manifold.

## 42. (Canceled)

43. (Currently Amended) The reactor according to Claim 42 41, wherein said second bundle is formed by at least two segments of tubes wound along helical

generatrices, nested and extending in parallel between said distributor and said manifold.

- 44. (Previously Presented) The reactor according to Claim 41, wherein said bundle is formed by three segments of tube wound along helical generatrices and nested.
- 45. (Previously Presented) The reactor according to Claim 41, wherein said segments have substantially the same length and/or induce substantially the same pressure drop on the flow of said coolant fluid, between said distributor and said manifold.

## 46. (Canceled)

- 47. (Currently Amended) The reactor according to Claim 46 41, wherein said distributor and/or said manifold being in the form of a torus and centered on said axis.
- 48. (Previously Presented) A reactor according to Claim 41, further comprising an agitator arranged around or inside said coil.
- 49. (Previously Presented) A reactor according to Claim 48, wherein said agitator is suspended from a ceiling of said reactor and forms a cage surrounding

said coil, the supply and evacuation of the coolant fluid towards or from said coil

50. (Currently Amended) A reactor according to Claim 42 41, wherein the

radius of said second bundle is less than that of said first bundle and being between

20 and 70% of the radius of said inner volume

being effected through the bottom of said reactor.

51. (Previously Presented) A reactor according to Claim 50, wherein the

radius of said second bundle is between 20 and 40% of said radius of said inner

volume.

52. (Previously Presented) A process for the treatment of a viscous medium

comprising the step of treading said liquid in a reactor as defined in Claim 41 and of

volume greater than about 8m<sup>3</sup>.

53. (Previously Presented) The process according to Claim 52, wherein said

treatment is a reaction of polymerization.

54. (Previously Presented) The process according to Claim 53, wherein the

reaction is a discontinuous reaction of polymerization.

55. (Previously Presented) The process according to Claim 53 wherein the

reaction is a continuous reaction of polymerization.

56. (Canceled)